

ASCOM T8

DESCRIPTION & APPLICATIONS

ASCOM T8 is a **talc powder** with chemical formula of $Mg_3Si_4O_{10}(OH)_2$.

have a low loss on ignition and a low iron content. Suitable for such applications where highest brightness is required.

Applications:

Paints, Ceramics, Paints & Coating, Cosmetics, Fertilizers, Cables, paper, Pharmaceuticals, Plastics, Body powder, TiO₂-spacer, whiteness booster of coatings and excellent anti block agent.

Standard Packaging:

20, 25 kg bag

Jumbo bag

Physical Properties (typical)

Whiteness:	
Brightness Ry (DIN 53163)	93 %
Refractive Index	1.57
Mohs Hardness	1
pH (ISO 787/9)	9 Max.
Oil absorption (ISO 787/5)	35 g/100g
Moisture	0.2% Max
Bulk Density	0.3 ± 0.03 gm/cm ³

Chemical Analysis (typical)

SiO ₂	55 %
MgO	33 %
CaO	0.6 %
Al ₂ O ₃	0.5 %
Fe ₂ O ₃	0.5 %
Na ₂ O	0.2 %
L.O.I	9 -11 %

General Product Data (typical)

D98	8 ± 0.5 μm
D50	2.4 ± 0.2 μm

The data in the Technical Data Sheet represents average values which are valid and reliable but not legally binding. ACCM disclaims any liability arising from damages or consequential loss. This Technical Data Sheet renders all previous versions invalid. (January 2021)

PARTICLE SIZE DISTRIBUTION (Sedigraph)

